

UltraHard Top P2 Plus®

Store Hazardous Drums Safely Outdoors With Pumps And Funnels In Place!

- Tall 23 3/4" head space easily accommodates rotary drum pumps and large conical funnels.
- Low profile (8 3/4") containment pallet positions drum-top funnels at a safe, convenient level to pour hazardous wastes.
- 100% polyethylene construction will not rust or corrode.
- Meets SPCC, EPA Container Storage Regulation 40 CFR 264.175 and UFC Spill Containment Regulations.
- Helps meet Stormwater Management Regulations — NPDES, 40 CFR 122.26 (1999).



Part# 9612



Ultra-Hard Top P2 Plus is lockable with a standard padlock, and can be safely lifted by forklift with drums in place.



"Swing out" lower doors provide full access to drums for loading and unloading — optional ramp features a non-slip surface.

Loading Ramp (Part# 0676) stores neatly inside the containment unit when not in use.

ULTRA-HARD TOP P2 PLUS

Ultra-Hard Top P2 Plus	Loading Ramp
Part# 9612: no drain Part# 9613: with drain	Part# 0676
Dimensions: 67 1/4" x 41 1/4" x 74" (1,708 mm x 1,047 mm x 1,880 mm)	Dimensions: 46" x 28" x 8 3/4" (1,168 mm x 711 mm x 222 mm)
Weight: 260 lbs. (118 kg)	Weight: 43 lbs. (19.5 kg)
Uniformly Distributed Load: 4,500 lbs. (2041 kg)	Surface: Non-slip
Containment Capacity: 66 gallons (250 L)	Construction: Polyethylene

U.S. Patent No. 5,615,608



What is a Best Management Practice (BMP)?

"Best Management Practices" include operating procedures and products to control site runoff, spills, leaks and drainage from raw material storage. When filing a Stormwater Pollution Prevention Plan (SWPPP), a detailed description of BMPs planned for use at the site is required. Please visit www.Stormwater-Products.com/regis for more information.