

SPILL MONKEY™

SECONDARY CONTAINMENT FILTRATION SYSTEM



Compact Versatile Spill Filtration

With its patented filter media and unique design, Spill Monkey is the ultimate barrier against oil and hydrocarbon contamination and a reliable guard against environmental damage.

Using gravity to filter diesel fuel, jet fuel, gasoline and transformer oil out of rainwater, the Spill Monkey allows operators to safely drain overflow from containers, water reservoirs and berms which need to remain empty to have the capacity to contain any spills.

Featuring an efficient sleek design and smart engineering, Spill Monkey allows for the fast draining of water while providing superior spill capacity. With its automatic shut off in the event of a massive spill, Spill Monkey is an essential addition for berms or any other area prone to oil and hydrocarbon spills.

Design Features

- Filtration stops contaminants, acting as a hydrocarbon selective unit for diesel fuel, jet fuel, gasoline and transformer oil
- Triangular end caps for stability on the ground
- Longer operational life
- Easy installation within seconds
- Ball valve with sight glass to monitor liquid levels and content
- Hydrocarbon capacity up to 650 cc of diesel fuel
- Feed end features a 3/4" (1.9 cm) camlock inlet
- Filter weight: 2.9 lb. (1.3 kg)

Additional Components

- 1 ft. chemical hose with camlock fittings
- 3/4" (1.9 cm) ball valve sight glass assembly with camlocks
- 3/4" (1.9 cm) bulkhead fitting to install on any berm (optional)

Specifications

Model	Dimensions	Avg. Flowrate at 6" Head Pressure	Capacity
Spill Monkey	7.6 cm x 30.5 cm 3" x 12"	150 LPH 40 GPH	650 cc



Spill Monkey is a product of Advanced Water Systems Inc. and is licenced for sale through SEI Industries Ltd.

West Coast Spill Supplies Ltd.
www.spillsupply.com

E-mail: sales@spillsupply.com Toll-free: 1.888.548.3800